



1
12a PARTIAL WALL SECTION
SCALE: 1" = 1'-0"

2
12a STIRRUP DETAIL
SCALE: 1" = 1'-0"

NOTES:

1. VARIATIONS IN IMPOSED LIVE & DEAD LOADS AND OTHER APPLICATION SPECIFIC VARIABLES REQUIRE ALL ASPECTS OF THE DETAILS SHOWN HERE TO BE DESIGNED AND /OR APPROVED BY A QUALIFIED ENGINEER
2. ALL CONSTRUCTION SHALL BE IN ACCORDANCE W/ THE SPECIFICATION OF AND THE RESPONSIBILITY OF A QUALIFIED STRUCTRURAL ENGINEER.
3. INSTALL APPROVED MEMBRANE WATER-PROOFING AT ALL SURFACES BELOW GRADE EXTEND 12" MIN. ABOVE FINAL GRADE

MINIMUM SPACING:

1. VENEER - 1000 lb/ft (15kN/m @ 18" (450mm)
2. VENEER - 1500 lb/ft (22kN/m @ 12" (300mm)

NOTE:

DUE TO VARIATIONS IN SELECTED PRINTER SETTINGS, NOTED SCALES MAY NO LONGER BE APPLICABLE

9701 N. Broadway Extension
Oklahoma City, Oklahoma 73114
www.buildblock.com

Office (405) 840-3386
Fax (405) 840-0625
Toll Free 1-866-222-2575

BASEMENT, TAPER UNIT & LOG WALL

DATE / REVISION	9-30-07 / 2	DETAIL SHEET 12a
SCALE	AS NOTED	
FILE NAME	BBDTL-12a.AEC	

Construction shall be built in accordance with all applicable local and national building codes. All drawings are subject to change without notice.