

# BUILDBLOCK® BUILDING SYSTEMS CANADIAN ENGINEERING TABLES

## METRIC STEEL / IMPERIAL SPACING

Wall Height	4" Walls Seismic Zones 0 - 4		6" & 8" Walls All Seismic Zones	
	Vertical	Horizontal	Vertical	Horizontal
8' Max 25% openings	10M @ 12"	10M @ 16"	10M @ 12"	15M @ 16"
8' Max 50% openings	10M @ 6"	10M @ 16"	10M @ 12"	15M @ 16"
10' Max 25% openings	10M @ 6"	10M @ 16"	10M @ 12"	15M @ 16"
12' Max 25% openings	NA	NA	10M @ 12"	15M @ 16"
12' Max 50% openings	NA	NA	15M @ 18"	15M @ 16"

Notes:

Table 3-A is based on the following assumptions:

Loads: wind, seismic, and gravity  
 Snow load: 1.9 kPa  
 Floor load: 1.9 kPa  
 Concrete: f'c at 28 days 20 MPa  
 Reinforcement: fy 400 MPa  
 Wall Openings: 2-15M all around



NOVATECH ENGINEERING



9701 N. Broadway Extension  
 Oklahoma City, Oklahoma 73114  
 www.buildblock.com

Office: (405) 840-3386  
 Fax: (831) 597-0792  
 Toll Free: 1(866) 222-2575

Reinforcement in Above  
 Grade 4", 6", and 8" Walls  
 NBC 1995 / OBC 1997

TABLE NUMBER

# 3-A